

# Fume Extractor



## Main Features

- ✓ Flexible Arm; enable to extend / retract and 360 degree swing.
- ✓ Large Cylinder type filter, Long lasting life.
- ✓ Z serial with hygienically pack filter.
- ✓ Low maintenance cost.
- ✓ Compact design; caster wheels with brake.
- ✓ Fume circulation design to prevent indoor cool air exhaust to out door.
- ✓ Low power energy saving.
- ✓ Low noise design.

*Fume Extractor LB-1200J and LB-xxxxZ serial is special design for extract the fume and dust directly at source. The polluted air is filtered and captured in an filter. The unit is equipped with a flexible suction hose and connect with a suction nozzle. Four caster wheels allow the unit easy to move to welding work site.*

## Technical Specifications

Model		LB-1200J	LB-1500Z	LB-2400Z	LB-3600Z
Maximum Airflow	(M3/h)	1,200	1,500	2,400	3,600
Motor Power	Kw	0.75	1.5	2.2	3.0
Input supply voltage	V/Ph/Hz	230/1/50	415/3/50		
Maximum filter area	M2	15	12	15	20
Filtration efficiency	%	99.7			
Noise level	db	60	60	68	72
Filter design		Self clean	Hygienically with auto reverse purging		
Dimension	LxWxH mm	480 x 580 x 1000	580 x 550 x 1250	580 x 550 x 1300	600 x 550 x 1750
Weight	Kg	48	65	75	90

*Note: Due to the continuous improvements of our products, the design and specifications are subjected to change without*