

# TIG WIRE FEEDER



SB-11P




SB-10-D



WFA4R

## Main Features

- ✓ Use the rollers of four to pressurize at the same time & driven by DC motor, the wire feed speed is smooth & steady.
- ✓ Fit with Euro tensile adjustable brake hub, can adjust the tensile force of the wire, permit 20 Kg of wire reel
- ✓ Able to feed : carbon steel, stainless steel, aluminum alloy welding wire diameter : 0.8 - 1.6mm.
- ✓ The self torch panel button control & all setting parameter with digital display , easy to use.
- ✓ Suitable use for TIG or Plasma welding, can cooperate with the welder to start the signal with 2T
- ✓ WFA4R model with two type function selection: Continue feed or intermittent feed the wire, auto wire retract feature provide.



## Options

- Hand torch attachment
- Machine torch attachment

Model	SB-10D	SB-11P	WFA4R
Input supply	AC-24V	AC-24V	AC-240V
Wire diameter	0.8 , 1.0 , 1.2 , 1.6 mm		
Wire feed speed	0.5 - 5m / min	0.5 - 5m / min	0.18 – 1.8m / min
Function control	Analog		Digital
Programmable	NiL		Yes
Auto-retract	Adjustable 0.9 – 9 sec		

Note: Due to the continuous improvements of our products, the design and specifications are subjected to change